

SAFETY DATA SHEET

Sterling Carburettor Cleaner

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Sterling Carburettor Cleaner

Product number GTSE-ACC4

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Car maintenance product.

1.3. Details of the supplier of the safety data sheet

Supplier Gocableties Ltd
 13 Somersall Lane
 Chesterfield
 Derbyshire
 S40 3LA

1.4. Emergency telephone number

Emergency telephone 01246 386 126

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture Classification

Physical hazards Aerosol 1 - H222, H229

Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H336 STOT RE 2 - H373

Environmental hazards Aquatic Chronic 3 - H412

Classification (67/548/EEC or 1999/45/EC) Xn;R20/21. Xi;R36/38. F+;R12. R52/53.

Human health Gas or vapour is harmful on prolonged exposure or in high concentrations. In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Deliberately concentrating and inhaling the contents of this container is dangerous and can be fatal.

Environmental This product contains substances which are very toxic or toxic to aquatic organisms and may cause long term effects to the aquatic environment (see sections 2 and 12)

Physicochemical Aerosol containers can explode when heated, due to excessive pressure build-up. The product is extremely flammable. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited.

2.2. Label elements

Pictogram



Signal word

Danger

Sterling Carburettor Cleaner

Classification Classification (67/548/EEC or 1999/45/EC) Flam. Liq. 2 - H225 Xn;R65. Xi;R38. F;R11. N;R51/53. R67.

Skin Irrit. 2 - H315

Asp. Tox. 1 - H304

STOT SE 3 - H336

Aquatic Chronic 2 - H411

XYLENE

CAS number: 1330-20-7

EC number: 215-535-7

REACH registration number:
012119488216-32-XXXX

10-30%

Classification (67/548/EEC or 1999/45/EC)
R10 Xn;R20/21 Xi;R38

Classification

Flam. Liq. 3 - H226

Acute Tox. 4 - H312

Acute Tox. 4 - H332

Skin Irrit. 2 - H315

Eye Irrit. 2 - H319

STOT SE 3 - H335

STOT RE 2 - H373

Asp. Tox. 1 - H304

Aquatic Chronic 3 - H412

ETHYLBENZENE

CAS number: 100-41-4

EC number: 202-849-4

REACH registration number:
012119489370-35

1-5%

Classification (67/548/EEC or 1999/45/EC)
F;R11 Xn;R20

Classification

Flam. Liq. 2 - H225

Acute Tox. 4 - H332

STOT RE 2 - H373

Asp. Tox. 1 - H304

Aquatic Chronic 3 - H412

HEXANE-norm

CAS number: 110-54-3

EC number: 203-777-6

REACH registration number:
012119480412-44

<1%

Classification (67/548/EEC or 1999/45/EC)
F;R11 Repr. Cat. 3;R62 Xn;R48/20,R65 Xi;R38 R67
N;R51/53

Classification

Flam. Liq. 2 - H225

STOT RE 2 - H373

Skin Irrit. 2 - H315

Repr. 2 - H361f

STOT SE 3 - H336

Asp. Tox. 1 - H304

Aquatic Chronic 2 - H411

TOLUENE

CAS number: 108-88-3

EC number: 203-625-9

REACH registration number:
012119471310-51

<1%

Sterling Carburettor Cleaner

Classification Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 Repr. 2 - H361d STOT SE 3 - H336 STOT RE 2 - H373 Asp. Tox. 1 - H304 Aquatic Chronic 3 - H412	Classification (67/548/EEC or 1999/45/EC) F;R11 Repr.Cat.3;R63 Xn;R48/20,R65 Xi;R38 R67
--	--

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Move affected person to fresh air at once.
Inhalation	If spray/mist has been inhaled, proceed as follows. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. If breathing stops, provide artificial respiration. Keep affected person warm and at rest. Get medical attention immediately.
Ingestion	Rinse mouth thoroughly with water. Do not induce vomiting. Get medical attention.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
---------------------	---

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
----------------------	------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with foam, carbon dioxide, dry powder or water fog.
------------------------------	--

5.2. Special hazards arising from the substance or mixture

Specific hazards	Extremely flammable. Forms explosive mixtures with air. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back. Containers can burst violently or explode when heated, due to excessive pressure buildup.
------------------	--

5.3. Advice for firefighters

Protective actions during firefighting	Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Use water to keep fire exposed containers cool and disperse vapours. Warn firefighters that aerosols are involved.
--	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Provide adequate ventilation. Use suitable respiratory protection if ventilation is inadequate. Avoid inhalation of vapours.
----------------------	--

6.2. Environmental precautions

Environmental precautions	Avoid the spillage or runoff entering drains, sewers or watercourses. Contain spillage with sand, earth or other suitable non-combustible material.
---------------------------	---

Sterling Carburettor Cleaner

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb spillage with non-combustible, absorbent material. Leave small quantities to evaporate, if safe to do so. Do not allow material to enter confined spaces, due to the risk of explosion.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Read and follow manufacturer's recommendations. Keep away from heat, sparks and open flame. Eliminate all sources of ignition. Do not spray on a naked flame or any incandescent material.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Extremely flammable. Keep away from heat, sparks and open flame. Store at moderate temperatures in dry, well ventilated area. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters Occupational exposure limits

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m³

Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m³

ACETONE

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m³

Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m³

HYDROCARBONS, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Long-term exposure limit (8-hour TWA): WEL 1200 mg/m³

XYLENE

Long-term exposure limit (8-hour TWA): WEL 50 ppm 220 mg/m³

Short-term exposure limit (15-minute): WEL 100 ppm 441 mg/m³

Sk

ETHYLBENZENE

Long-term exposure limit (8-hour TWA): WEL 100 ppm(Sk) 441 mg/m³(Sk)

Short-term exposure limit (15-minute): WEL 125 ppm(Sk) 552 mg/m³(Sk)

HEXANE-norm

Long-term exposure limit (8-hour TWA): WEL 20 ppm 72 mg/m³

TOLUENE

Long-term exposure limit (8-hour TWA): WEL 50 ppm 191 mg/m³

Short-term exposure limit (15-minute): WEL 100 ppm 384 mg/m³

Sk

WEL = Workplace Exposure Limit Sk =

Can be absorbed through the skin.

Ingredient comments WEL = Workplace Exposure Limits

XYLENE (CAS: 1330-20-7)

Sterling Carburettor Cleaner

DNEL	Consumer - Oral; Long term systemic effects: 12.5 mg/kg/day Consumer - Dermal; Long term systemic effects: 1872 mg/kg/day Consumer - Inhalation; Long term systemic effects: 65.3 mg/m ³ Consumer - Inhalation; Short term : 260 mg/m ³ Industry - Dermal; Long term systemic effects: 3182 mg/kg/day Industry - Inhalation; Long term systemic effects: 221 mg/m ³ Industry - Inhalation; Short term : 442 mg/m ³
PNEC	This product is a UVCB substance and its composition will be variable, so reported properties may vary or require a range of values to describe them. - Fresh water; 0.327 mg/l - Marine water; 0.327 mg/l - Intermittent release; 0.327 mg/l - STP; 6.58 mg/l - Sediment (Freshwater); 12.46 mg/kg - Sediment (Marinewater); 12.46 mg/kg - Soil; 2.31 mg/kg

TOLUENE (CAS: 108-88-3)

DNEL	General population - Inhalation; : 226 mg/m ³
PNEC	- Fresh water; 0.68 mg/l - Marine water; 0.68 mg/l - Soil; 2.89 mg/kg

8.2. Exposure controls

Appropriate engineering occupational exposure limits for the product or ingredients	Provide adequate ventilation. Avoid inhalation of vapours and spray/mists. Observe any controls
Personal protection	When using do not smoke.
Eye/face protection	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles.
Hand protection	Due to the packaging form, aerosol, risk of skin contact is small. Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. It is recommended that gloves are made of the following material: Nitrile rubber. Polyvinyl alcohol (PVA). Viton rubber (fluoro rubber). The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material.
Hygiene measures	Wash hands after handling. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Use appropriate hand lotion to prevent defatting and cracking of skin.
Respiratory protection	If ventilation is inadequate, suitable respiratory protection must be worn.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Aerosol.
Colour	Clear.
Odour	Organic solvents.
Initial boiling point and range	-40 to -2°C @ 1013 hPa
Flash point	<-40°C

Sterling Carburettor Cleaner

Upper/lower flammability or explosive limits	Lower : 1.8% - Upper 9.5%
Vapour pressure	ca. 590 to 1760 kPa @ 45°C
Vapour density	ca. 1.5 at 15°C
Partition coefficient	log Pow: ca. 2.3 to 2.8
Auto-ignition temperature	410-580°C
Comments	Information given is applicable to the major ingredient.

9.2. Other information

Other information	Not available.
Volatile organic compound	This product contains a maximum VOC content of 660 g/l.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	Stable at normal ambient temperatures and when used as recommended.
------------	---

10.2. Chemical stability

Stability	Avoid the following conditions: Heat, sparks, flames.
-----------	---

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Does not decompose when used and stored as recommended.
------------------------------------	---

10.4. Conditions to avoid

Conditions to avoid	Avoid heat, flames and other sources of ignition. Avoid exposing aerosol containers to high temperatures or direct sunlight.
---------------------	--

10.5. Incompatible materials

Materials to avoid	Keep away from oxidising materials, heat and flames.
--------------------	--

10.6. Hazardous decomposition products

Hazardous decomposition products Does not decompose when used and stored as recommended. Thermal decomposition or products combustion products may include the following substances: Toxic and corrosive gases or vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects Acute toxicity - dermal

ATE dermal (mg/kg)	5,500.0
--------------------	---------

Acute toxicity - inhalation

ATE inhalation (vapours mg/l)	55.0
-------------------------------	------

General information	Deliberately concentrating and inhaling the contents of this container is dangerous and can be fatal.
Inhalation	In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Unconsciousness, possibly death.
Skin contact	Harmful in contact with skin.
Eye contact	Irritating to eyes. Vapour or spray in the eyes may cause irritation and smarting.

Sterling Carburettor Cleaner

Acute and chronic health hazards	Arrhythmia (deviation from normal heart beat). Irritating to skin. Irritating to eyes. In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea.
Route of entry	Inhalation
Target organs	Central nervous system Respiratory system, lungs
Medical symptoms	Skin irritation. Arrhythmia (deviation from normal heart beat). Narcotic effect. Vapours may cause drowsiness and dizziness. Irritation of eyes

SECTION 12: Ecological Information

Ecotoxicity	This product has not been tested but contains ingredients which are toxic or very toxic to aquatic organisms and may cause long term adverse effects in the aquatic environment. During normal use the volatility of the components and the packaging form, pressurised container, make entry into the aquatic environment unlikely, however, do not empty or discharge into drains or watercourses. Ensure container is empty before disposal to prevent contents entering watercourses.
-------------	---

12.1. Toxicity

Toxicity	Not available.
----------	----------------

12.2. Persistence and degradability

Persistence and degradability	Not available.
-------------------------------	----------------

12.3. Bioaccumulative potential

Bioaccumulative potential	Not available.
Partition coefficient	log Pow: ca. 2.3 to 2.8

12.4. Mobility in soil

Mobility	Not known.
----------	------------

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment	Not available.
------------------------------------	----------------

12.6. Other adverse effects

Other adverse effects	Not available.
-----------------------	----------------

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information	Do not puncture or incinerate, even when empty.
Disposal methods	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Containers should be thoroughly emptied before disposal because of the risk of an explosion. Empty containers must not be punctured or incinerated because of the risk of an explosion.

SECTION 14: Transport information

General	This product is packed in accordance with the Limited Quantity Provisions of CDGCPL2, ADR and IMDG. These provisions allow transport of aerosols of less than 1 litre packed in cartons of less than 30kg gross weight to be exempt from control providing that they are labelled in accordance with the requirements of these regulations to show that they are being transported as Limited Quantities. Aerosols not so packed and labelled must show the following.
---------	--

14.1. UN number

UN No. (ADR/RID)	1950
------------------	------

Sterling Carburettor Cleaner

UN No. (IMDG) 1950

UN No. (ICAO) 1950

14.2. UN proper shipping name

Proper shipping name (ADR/RID) AEROSOLS

Proper shipping name (IMDG) AEROSOLS

Proper shipping name (ICAO) AEROSOLS

Proper shipping name (ADN) AEROSOLS

14.3. Transport hazard class(es)

ADR/RID class 2.1

ADR/RID label 2.1

IMDG class 2.1

ICAO class/division 2.1

Transport labels

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

EmS F-D, S-U

Tunnel restriction code (D)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).

EU legislation Commission Regulation (EU) No 453/2010 of 20 May 2010.

Guidance Workplace Exposure Limits EH40.
CHIP for everyone HSG228.
Safety Data Sheets for Substances and Preparations.
Approved Classification and Labelling Guide (Sixth edition) L131.
British Aerosol Manufacturers Code of Practice 7th. Edition 1999

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Sterling Carburettor Cleaner

Revision comments Supplemental information added.
 Revision date 18/11/2015
 Revision 2

SDS number 12652

SDS status Approved.

Risk phrases in full R10 Flammable.
 R11 Highly flammable.
 R12 Extremely flammable.
 R20/21 Harmful by inhalation and in contact with skin.
 R36 Irritating to eyes.
 R36/38 Irritating to eyes and skin.
 R38 Irritating to skin.
 R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
 R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
 R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
 R62 Possible risk of impaired fertility.
 R65 Harmful: may cause lung damage if swallowed.
 R66 Repeated exposure may cause skin dryness or cracking.
 R67 Vapours may cause drowsiness and dizziness.
 Hazard statements in full H220 Extremely flammable gas.
 H222 Extremely flammable aerosol.
 H225 Highly flammable liquid and vapour.
 H226 Flammable liquid and vapour.
 H229
 Pressurised container: may burst if heated
 H304 May be fatal if swallowed and enters airways.
 H312 Harmful in contact with skin.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H332 Harmful if inhaled.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.
 H361d Suspected of damaging the unborn child.
 H361f Suspected of damaging fertility.
 H373 May cause damage to organs through prolonged or repeated exposure.
 H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.