

# SAFETY DATA SHEET

## White Grease

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name                      White Grease  
 Product number                  GTSE-AWG4

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses                    Grease.

#### 1.3. Details of the supplier of the safety data sheet

Supplier                            Gocableties Ltd  
    13 Somersall Lane  
    Chesterfield  
    Derbyshire  
    S40 3LA

#### 1.4. Emergency telephone number

Emergency telephone            01246 386 126

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture Classification

Physical hazards                  Aerosol 1 - H222, H229  
 Health hazards                    Skin Irrit. 2 - H315 STOT SE 3 - H336  
 Environmental hazards          Aquatic Chronic 2 - H411

Classification (67/548/EEC or 1999/45/EC)    Xi;R38. F+;R12. N;R51/53. R67.

Human health                      Gas or vapour is harmful on prolonged exposure or in high concentrations. In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Deliberately concentrating and inhaling the contents of this container is dangerous and can be fatal.

Environmental                      This product contains substances which are very toxic or toxic to aquatic organisms and may cause long term effects to the aquatic environment (see sections 2 and 12)

Physicochemical                    Aerosol containers can explode when heated, due to excessive pressure build-up. The product is extremely flammable. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited.

#### 2.2. Label elements

Pictogram



Signal word

Danger

Hazard statements

H222 Extremely flammable aerosol.  
 H229 Pressurised container: may burst if heated  
 H315 Causes skin irritation.  
 H336 May cause drowsiness or dizziness.  
 H411 Toxic to aquatic life with long lasting effects.

## White Grease

Precautionary statements      P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.  
 No smoking.  
 P211 Do not spray on an open flame or other ignition source.  
 P251 Do not pierce or burn, even after use.  
 P271 Use only outdoors or in a well-ventilated area.  
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
 P102 Keep out of reach of children.  
 P501 Dispose of contents/container in accordance with local regulations.  
 P260 Do not breathe vapour/spray.  
 P262 Do not get in eyes, on skin, or on clothing.

Contains                              HYDROCARBONS, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

### 2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS CAS number: 68476-85-7                              EC number: 270-704-2	30-60%
Classification Flam. Gas 1 - H220 Press. Gas, Liquefied - H280	Classification (67/548/EEC or 1999/45/EC) F+;R12 Carc. Cat. 1;R45 Muta. Cat. 2;R46
HYDROCARBONS, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane CAS number: —    EC number: 921-024-6                              REACH registration number: 01-2119475514-35	10-30%
Classification Skin Irrit. 2 - H315 Asp. Tox. 1 - H304 STOT SE 3 - H336 Aquatic Chronic 2 - H411	Classification (67/548/EEC or 1999/45/EC) Flam. Liq. 2 - H225 Xn;R65. Xi;R38. F;R11. N;R51/53. R67.
ZINC OXIDE CAS number: 1314-13-2                              EC number: 215-222-5                              REACH registration number: 012119463881-32  M factor (Acute) = 1                              M factor (Chronic) = 1	1-5%
Classification Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410	Classification (67/548/EEC or 1999/45/EC) N;R50/53
HEXANE-norm CAS number: 110-54-3                              EC number: 203-777-6                              REACH registration number: 012119480412-44	<1%

## White Grease

Classification  
 Flam. Liq. 2 - H225  
 STOT RE 2 - H373  
 Skin Irrit. 2 - H315  
 Repr. 2 - H361f  
 STOT SE 3 - H336  
 Asp. Tox. 1 - H304  
 Aquatic Chronic 2 - H411

Classification (67/548/EEC or 1999/45/EC)  
 F;R11 Repr. Cat. 3;R62 Xn;R48/20,R65 Xi;R38 R67  
 N;R51/53

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

General information	Move affected person to fresh air at once.
Inhalation	If spray/mist has been inhaled, proceed as follows. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. If breathing stops, provide artificial respiration. Keep affected person warm and at rest. Get medical attention immediately.
Ingestion	Rinse mouth thoroughly with water. Do not induce vomiting. Get medical attention.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
---------------------	---

#### 4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
----------------------	------------------------

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media	Extinguish with foam, carbon dioxide, dry powder or water fog.
------------------------------	--

#### 5.2. Special hazards arising from the substance or mixture

Specific hazards	Extremely flammable. Forms explosive mixtures with air. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back. Containers can burst violently or explode when heated, due to excessive pressure buildup.
------------------	--

#### 5.3. Advice for firefighters

Protective actions during firefighting	Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Use water to keep fire exposed containers cool and disperse vapours. Warn firefighters that aerosols are involved.
--	--

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Provide adequate ventilation. Use suitable respiratory protection if ventilation is inadequate. Avoid inhalation of vapours.
----------------------	--

#### 6.2. Environmental precautions

Environmental precautions	Avoid the spillage or runoff entering drains, sewers or watercourses. Contain spillage with sand, earth or other suitable non-combustible material.
---------------------------	---

## White Grease

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up      Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb spillage with non-combustible, absorbent material. Leave small quantities to evaporate, if safe to do so. Do not allow material to enter confined spaces, due to the risk of explosion.

### 6.4. Reference to other sections

Reference to other sections      For personal protection, see Section 8. For waste disposal, see Section 13.

## **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Usage precautions      Read and follow manufacturer's recommendations. Keep away from heat, sparks and open flame. Eliminate all sources of ignition. Do not spray on a naked flame or any incandescent material.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage precautions      Extremely flammable. Keep away from heat, sparks and open flame. Store at moderate temperatures in dry, well ventilated area. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

### 7.3. Specific end use(s)

Specific end use(s)      The identified uses for this product are detailed in Section 1.2.

## **SECTION 8: Exposure Controls/personal protection**

### 8.1. Control parameters Occupational exposure limits

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m<sup>3</sup> Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m<sup>3</sup>

HYDROCARBONS, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Long-term exposure limit (8-hour TWA): WEL 1200 mg/m<sup>3</sup>

HEXANE-norm

Long-term exposure limit (8-hour TWA): WEL 20 ppm 72 mg/m<sup>3</sup>

WEL = Workplace Exposure Limit

Ingredient comments      WEL = Workplace Exposure Limits

### 8.2. Exposure controls

Appropriate engineering controls      Provide adequate ventilation. Avoid inhalation of vapours and spray/mists. Observe any occupational exposure limits for the product or ingredients.

Personal protection      When using do not smoke.

Eye/face protection      Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles.

Hand protection      Due to the packaging form, aerosol, risk of skin contact is small. Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. It is recommended that gloves are made of the following material: Nitrile rubber. Polyvinyl alcohol (PVA). Viton rubber (fluoro rubber). The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material.

Hygiene measures      Wash hands after handling. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Use appropriate hand lotion to prevent defatting and cracking of skin.

Respiratory protection      If ventilation is inadequate, suitable respiratory protection must be worn.

## White Grease

### SECTION 9: Physical and Chemical Properties

#### 9.1. Information on basic physical and chemical properties

Appearance	Aerosol.
Colour	Clear.
Odour	Organic solvents.
Initial boiling point and range	-40 to -2°C @ 1013 hPa
Flash point	<-40°C
Upper/lower flammability or explosive limits	Lower : 1.8% - Upper 9.5%
Vapour pressure	ca. 590 to 1760 kPa @ 45°C
Vapour density	ca. 1.5 at 15°C
Partition coefficient	log Pow: ca. 2.3 to 2.8
Auto-ignition temperature	410-580°C
Comments	Information given is applicable to the major ingredient.

#### 9.2. Other information

Other information	Not available.
Volatile organic compound	This product contains a maximum VOC content of 474 g/l.

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Reactivity Stable at normal ambient temperatures and when used as recommended.

#### 10.2. Chemical stability

Stability Avoid the following conditions: Heat, sparks, flames.

#### 10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Does not decompose when used and stored as recommended.

#### 10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid exposing aerosol containers to high temperatures or direct sunlight.

#### 10.5. Incompatible materials

Materials to avoid Keep away from oxidising materials, heat and flames.

#### 10.6. Hazardous decomposition products

Hazardous decomposition products Does not decompose when used and stored as recommended. Thermal decomposition or products combustion products may include the following substances: Toxic and corrosive gases or vapours.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

## White Grease

General information	Deliberately concentrating and inhaling the contents of this container is dangerous and can be fatal.
Inhalation	In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Unconsciousness, possibly death.
Skin contact	Irritating to skin.
Eye contact	Vapour or spray in the eyes may cause irritation and smarting.
Acute and chronic health hazards	Arrhythmia (deviation from normal heart beat). Irritating to skin. In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea.
Route of entry	Inhalation
Target organs	Central nervous system Respiratory system, lungs
Medical symptoms	Skin irritation. Arrhythmia (deviation from normal heart beat). Narcotic effect. Vapours may cause drowsiness and dizziness.

### SECTION 12: Ecological Information

Ecotoxicity	This product has not been tested but contains ingredients which are toxic or very toxic to aquatic organisms and may cause long term adverse effects in the aquatic environment. During normal use the volatility of the components and the packaging form, pressurised container, make entry into the aquatic environment unlikely, however, do not empty or discharge into drains or watercourses. Ensure container is empty before disposal to prevent contents entering watercourses.
-------------	---

#### 12.1. Toxicity

Toxicity	Not available.
----------	----------------

#### 12.2. Persistence and degradability

Persistence and degradability	Not available.
-------------------------------	----------------

#### 12.3. Bioaccumulative potential

Bioaccumulative potential	Not available.
---------------------------	----------------

Partition coefficient	log Pow: ca. 2.3 to 2.8
-----------------------	-------------------------

#### 12.4. Mobility in soil

Mobility	Not known.
----------	------------

#### 12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment	Not available.
------------------------------------	----------------

#### 12.6. Other adverse effects

Other adverse effects	Not available.
-----------------------	----------------

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

General information	Do not puncture or incinerate, even when empty.
Disposal methods	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Containers should be thoroughly emptied before disposal because of the risk of an explosion. Empty containers must not be punctured or incinerated because of the risk of an explosion.

## White Grease

### SECTION 14: Transport information

**General** This product is packed in accordance with the Limited Quantity Provisions of CDGCPL2, ADR and IMDG. These provisions allow transport of aerosols of less than 1 litre packed in cartons of less than 30kg gross weight to be exempt from control providing that they are labelled in accordance with the requirements of these regulations to show that they are being transported as Limited Quantities. Aerosols not so packed and labelled must show the following.

#### 14.1. UN number

UN No. (ADR/RID) 1950

UN No. (IMDG) 1950

UN No. (ICAO) 1950

#### 14.2. UN proper shipping name

Proper shipping name (ADR/RID) AEROSOLS (HYDROCARBONS, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane)

Proper shipping name AEROSOLS (HYDROCARBONS, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane) (IMDG)

Proper shipping name (ICAO) AEROSOLS (HYDROCARBONS, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane)

Proper shipping name (ADN) AEROSOLS (HYDROCARBONS, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane)

#### 14.3. Transport hazard class(es)

ADR/RID class 2.1

ADR/RID label 2.1

IMDG class 2.1

ICAO class/division 2.1

Transport labels



#### 14.4. Packing group

Not applicable.

#### 14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



#### 14.6. Special precautions for user

EmS F-D, S-U

Tunnel restriction code (D)

#### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and the IBC Code

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).

EU legislation Commission Regulation (EU) No 453/2010 of 20 May 2010.

## White Grease

Guidance                      Workplace Exposure Limits EH40.  
                                     CHIP for everyone HSG228.  
                                     Safety Data Sheets for Substances and Preparations.  
                                     Approved Classification and Labelling Guide (Sixth edition) L131.  
                                     British Aerosol Manufacturers Code of Practice 7th. Edition 1999

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

<b>SECTION 16: Other information</b>
--------------------------------------

Revision date 18/11/2015

Revision 2

SDS number 12674

SDS status Approved.

Risk phrases in full	<p>R11 Highly flammable.          R12 Extremely flammable.          R38 Irritating to skin.          R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.          R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.          R62 Possible risk of impaired fertility.          R65 Harmful: may cause lung damage if swallowed.          R67 Vapours may cause drowsiness and dizziness.</p>
Hazard statements in full	<p>H220 Extremely flammable gas.          H222 Extremely flammable aerosol.          H222 Extremely flammable aerosol.          H225 Highly flammable liquid and vapour.          H225 Highly flammable liquid and vapour.          H229 Pressurised container: may burst if heated          H229 Pressurised container: may burst if heated          H280 Contains gas under pressure; may explode if heated.          H304 May be fatal if swallowed and enters airways.          H304 May be fatal if swallowed and enters airways.          H315 Causes skin irritation.          H315 Causes skin irritation.          H336 May cause drowsiness or dizziness.</p>



## White Grease

H336 May cause drowsiness or dizziness.

H361f Suspected of damaging fertility.

H361f Suspected of damaging fertility.

H373 May cause damage to organs through prolonged or repeated exposure.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.