



3:1 Adhesive Lined Heat Shrink

Product features:

- Flexible adhesive lined heat shrink manufactured to give a moisture proof seal in a wide range of applications.
- **Chemical resistance:** Fuel, hydraulic fluid and lubricating oil.

Technical Information	
Shrink Ratio:	3:1
Operating Temperature	-55°C to +125°C
Material	Polyolefin - Dual wall adhesive lined
Shrink Properties	Shrinkable temperature: 80°C, Longitudinal shrinking less than 5%
Diameter	3.2-39mm
Application	Sealing electrical components, cable harnesses, cable ends and splices



GTSE SKU	Color	Length(m)	Supplied Internal Diameter Min. (mm)	Recovered Internal Diameter Min. (mm)	Wall Thickness After Recovery (mm)	Adhesive Thickness (mm)
GCT31HST32BLA	■	150	3.2	1.1	1.00(±0.28)	0.30
GCT31HST48BLA	■	75	4.8	1.6	1.00(±0.28)	0.30
GCT31HST64BLA	■	60	6.4	2.1	1.00(±0.28)	0.30
GCT31HST95BLA	■	60	9.5	3.2	1.40(±0.28)	0.45
GCT31HST127BLA	■	25	12.7	4.2	1.78(±0.38)	0.53
GCT31HST191BLA	■	25	19.1	6.4	2.25(±0.55)	0.68
GCT31HST254BLA	■	25	25.4	8.4	2.54(±0.55)	0.76
GCT31HST390BLA	■	25	39.0	12.7	2.54(±0.55)	0.76
GCT31HSTL32BLA	■	1.2	3.2	1.1	1.00(±0.28)	0.30
GCT31HSTL48BLA	■	1.2	4.8	1.6	1.00(±0.28)	0.30
GCT31HSTL64BLA	■	1.2	6.4	2.1	1.00(±0.28)	0.30
GCT31HSTL95BLA	■	1.2	9.5	3.2	1.40(±0.28)	0.45
GCT31HSTL127BLA	■	1.2	12.7	4.2	1.78(±0.38)	0.53
GCT31HSTL191BLA	■	1.2	19.1	6.4	2.25(±0.55)	0.68
GCT31HSTL254BLA	■	1.2	25.4	8.4	2.54(±0.55)	0.76
GCT31HSTL391BLA	■	1.2	39.0	12.7	2.54(±0.55)	0.76