





Ring Terminals

Product features:

- Flared barrel for easy wire insertion
- Low insertion force and easy crimping whilst ensuring secure termination
- Long-term performance, easy installation, and a low installed cost

Technical Information	
Operating Temperature	-10°C to +75°C.
Material	Insulation: Vinyl Terminal Body: Copper Plating: Tin.
Voltage rating:	600V
current rating	Red - 19A, Blue - 27A, Yellow - 48A


Ring Terminals with Copper Sleeve

Standard Ring Terminals

Material

- ① Copper
- ② Tin
- ③ Vinyl
- ④ Copper

GTSE SKU	Colour	Wire Range (mm ²)	Dimensions (mm)						
			D	d1	d2	W	L	E	F
GCTR32R	Red	0.5-1.5	4.3	1.7	3.3	5.5	17.5	10.0	4.8
GCTR37R	Red	0.5-1.5	4.3	1.7	3.8	5.5	17.5	10.0	4.8
GCTR43R	Red	0.5-1.5	4.3	1.7	4.4	6.6	19.4	10.0	6.3
GCTR53R	Red	0.5-1.5	4.3	1.7	5.4	8.0	20.8	10.0	7.0
GCTR53RL	Red	0.5-1.5	4.3	1.7	5.4	8.0	20.8	10.0	7.0
GCTR63R	Red	0.5-1.5	4.3	1.7	6.5	11.6	26.7	10.0	11.0
GCTR63RL	Red	0.5-1.5	4.3	1.7	6.5	11.6	26.7	10.0	11.0
GCTR84R	Red	0.5-1.5	4.3	1.7	8.5	11.6	26.7	10.0	11.0
GCTR84L	Red	0.5-1.5	4.3	1.7	8.5	11.6	26.7	10.0	11.0
GCTR105R	Red	0.5-1.5	4.3	1.7	10.5	13.6	30.5	10.0	13.9
GCTR130R	Red	0.5-1.5	4.3	1.7	13.0	18.0	35.4	10.0	15.2
GCTR32B	Blue	1.5-2.5	4.8	2.3	3.3	6.6	17.8	10.0	4.7
GCTR37B	Blue	1.5-2.5	4.8	2.3	3.8	6.6	17.8	10.0	4.7

GTSE SKU	Colour	Wire Range (mm ²)	Dimensions (mm)						
			D	d1	d2	W	L	E	F
GCTR43B		1.5-2.5	4.8	2.3	4.4	6.6	21.8	10.0	6.3
GCTR53B		1.5-2.5	4.8	2.3	5.4	8.5	21.8	10.0	7.8
GCTR53BL		1.5-2.5	4.8	2.3	5.4	8.5	21.8	10.0	7.8
GCTR64B		1.5-2.5	4.8	2.3	6.4	12.0	26.8	10.0	11.0
GCTR64BL		1.5-2.5	4.8	2.3	6.4	12.0	26.8	10.0	11.0
GCTR84B		1.5-2.5	4.8	2.3	8.4	12.0	26.8	10.0	11.0
GCTR84BL		1.5-2.5	4.8	2.3	8.4	12.0	26.8	10.0	11.0
GCTR105B		1.5-2.5	4.8	2.3	10.5	13.6	30.5	10.0	13.9
GCTR130B		1.5-2.5	4.8	2.3	13.0	19.2	35.4	10.0	15.2
GCTR37Y		4.0-6.0	6.7	3.4	3.7	7.2	22.7	13.0	6.1
GCTR43Y		4.0-6.0	6.7	3.4	4.4	7.2	23.2	13.0	6.1
GCTR53Y		4.0-6.0	6.7	3.4	5.4	9.5	27.3	13.0	8.3
GCTR64Y		4.0-6.0	6.7	3.4	6.4	12.0	29.5	13.0	11.2
GCTR64YL		4.0-6.0	6.7	3.4	6.4	12.0	29.5	13.0	11.2
GCTR84Y		4.0-6.0	6.7	3.4	8.5	15.0	34.5	13.0	13.5
GCTR84YL		4.0-6.0	6.7	3.4	8.5	15.0	34.5	13.0	13.5
GCTR105Y		4.0-6.0	6.7	3.4	10.6	15.0	34.5	13.0	13.5
GCTR105YL		4.0-6.0	6.7	3.4	10.6	15.0	34.5	13.0	13.5
GCTR130Y		4.0-6.0	6.7	3.4	13.0	19.2	39.1	13.0	16.0