

# Duct Tape



Product features:

- Ideal for binding, repairs and securely fixing things onto surfaces
- Strong adhesive coating with vacuum hotmelt (synthetic rubber)
- Leaves no residue when removed
- Water resistant
- Available in black, red, silver and white
- Suitable for indoor and outdoor use



Technical Information

QuantitySupplied in single rolls

MaterialPolycloth

AdhesiveSynthetic rubber

• Adhesive to steel> 6 N/cm











Total thickness0.18 mm (±0.01)

Elongation10-20%

Tensile strength60 N/cm

Roll back tack> 6 (ball no.)

Temperature rating-15°C to +70°C

Width (mm) x Length (m)	Thickness (mm)	Box Quantity*	SKU	Colour
48 x 50	0.18	24	GCTDUC5048	   
75 x 50	0.18	16	GTSE-DUC5075	  
100 x 50	0.18	12	GTSE-DUC50100	  

\*Box quantity refers to quantity of individual rolls.

Disclaimer Notice

The above information is given only as a guide, the user should ensure that the performance of the product is sufficient for application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. GTSE cannot be held responsible for product failure unless full testing has been carried out. The user has to decide on the tapes suitability for their own applications.