

Aluminium Foil Tape

ROHS





Product features:

- Perfect for joining and sealing insulation, ducting & pipework
- Creates an air and watertight seal to protect against water leakages
- Flame, Water and UV Resistant
- Available in a range of widths and lengths to suit different applications
- · Suitable for indoor and outdoor use



Technical Information				
Quantity	Supplied in single rolls			
Material	Aluminium foil			
Adhesive	Release paper carrier with acrylic emulsion based adhesive			
Adhesive to steel	> 4 N/cm			
Total thickness	0.05 mm			
Tensile strength	> 12 N/cm			
Roll back tack	> 3 (ball no.)			
Temperature rating	-15°C to +70°C			

Width (mm) x Length (m)	Thickness (mm)	Box Quantity*	SKU	Colour
48 x 10	0.05	48	GCTAFT1048	
48 x 25	0.05	36	GCTAFT2548	
48 x 50	0.05	24	GCTAFT5048	
75 x 50	0.05	16	GCTAFT5075	
100 x 50	0.05	12	GCTAFT50100	

^{*}Box quantity refers to quantity of individual rolls.

Disclaimer Notice

The above information is given only as a guide, the user should ensure that the performance of the product is sufficient for application.

The quoted values are average and should not be taken as maximum or minimum values for specific purposes.

GTSE cannot be held responsible for product failure unless full testing has been carried out.

The user has to decide on the tapes suitability for their own applications.

Email: sales@gtse.co.uk
Tel: 01246 386 126