

# Masking Tape



## Product features:

- General purpose masking tape used when painting and decorating to protect window sills and skirting boards
- Provides good resistance to bleed-through, enabling crisp, straight paint lines
- Can easily be removed without leaving residue

## Technical Information

Quantity	Supplied in single rolls
Material	Crepe paper with natural rubber adhesive
Adhesive	Rubber based
• Adhesive to steel	2-2.4 N/cm
Total thickness	0.12mm (±0.02)
Tensile strength	22-28 N/cm
Roll back tack	≥ 5 (ball no.)
Temperature rating	-50°C to +70°C

Width (mm) x Length (m)	Thickness (mm)	Box Quantity*	SKU	Colour
19 x 25	0.12	90	GCTMT2519WHI	<input type="checkbox"/>
19 x 50	0.12	60	GCTMT5019WHI	<input type="checkbox"/>
25 x 50	0.12	48	GCTMT5025WHI	<input type="checkbox"/>
38 x 50	0.12	60	GCTMT5038WHI	<input type="checkbox"/>
50 x 50	0.12	24	GCTMT5050WHI	<input type="checkbox"/>
75 x 50	0.12	16	GTSE-MT7550WHI	<input type="checkbox"/>
100 x 50	0.12	12	GTSE-MT10050WHI	<input type="checkbox"/>

\*Box quantity refers to quantity of individual rolls.

### Disclaimer Notice

The above information is given only as a guide, the user should ensure that the performance of the product is sufficient for application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. GTSE cannot be held responsible for product failure unless full testing has been carried out. The user has to decide on the tapes suitability for their own applications.