

## **PVC Non Adhesive Tape**

## **Product features:**

- Manufactured using premium grade PVC
- Flexible with excellent protection against abrasion
- Moisture and UV resistant, flame retardant
- Doesn't leave behind a mark like traditional adhesive tape
- · Suitable for indoor and outdoor use



Technical Information		
Quantity	Supplied in single rolls	
Material	Premium grade PVC	
Total thickness	0.13 mm (±0.005)	
Elongation	220%	
Tensile strength	15 N/cm	
Temperature rating	Up to 80°C	
Voltage resistance	600 V	
Low speed unwind force	2.2-4.4 N/cm	
Flame retardancy	Self extinguishing	
Dielectric strength	40 kV/mm	
Compliance	Conforms to BSEN 60454-3-1 standards	

Width (mm) x Length (m)	Thickness (mm)	Box Quantity*	SKU	Colour
19 x 40	0.13	120	GTSE-NPVC1940B	

<sup>\*</sup>Box quantity refers to quantity of individual rolls.

## Disclaimer Notice

The above information is given only as a guide, the user should ensure that the performance of the product is sufficient for application.

The quoted values are average and should not be taken as maximum or minimum values for specific purposes.

GTSE cannot be held responsible for product failure unless full testing has been carried out.

The user has to decide on the tapes suitability for their own applications.

Email: <a href="mailto:sales@gtse.co.uk">sales@gtse.co.uk</a>
Tel: 01246 386 126